



REFERENCE STANDARD 4.5

SPECIFICATIONS

SPEAKERS:

- Frequency Response: 24 through 32,000 Hz ± 3 dB
- Amplifier Power: Bi-amping, minimum 100 watts per channel for bass section, 75 for midrange and high frequency. Single amp. Minimum 100 watts per channel
- Nominal Impedance: 4 ohms
- Drivers: For each channel:
 - (a) two 12-inch (30cm) Infinity-Watkins Dual-Drive Woofer with polypropylene cones;
 - (b) four EMIM (Electromagnetic Induction Midrange) drivers in a dipole configuration;
 - (c) four EMIT (Electromagnetic Induction Tweeters), one of them facing rearward
- Crossover Frequencies: 150Hz (adjustable with optional electronic crossover control) and 5,000 Hz
- Dimensions: 64 1/2 inches x 26 1/2 wide x 14 1/2 (160.6 cm x 66.25 wide x 36.25)
- Shipping Weight: 117 pounds (53 kgs) each
- Finish: Solid oak and veneers. Cloth grille and its frame are removable
- Warranty: Five years, transferable (see complete warranty statement)

CONTROL UNIT:

Dimensions: 10 1/4 inches x 14 1/4 wide x 2 1/8 (26 cm x 36.2 wide x 5.4)

PRODUCTION HISTORY:

- Introduced in 1978
- Discontinued in 1982
- Original Retail Price: \$4,500.00

PHYSICAL SPECIFICATIONS:

COSMETIC PARTS:

Grille Assy. Bottom .025...0352

CROSSOVER PARTS:


Pot 2 Ohm 50W .145...0243
 Fuse 2A AGC .870...0024
 Fuse Holder .550...0062

DRIVERS (TRANSDUCERS)

EMIM Mid Rev. B/C .902...0012C
 EMIT Twt Sq/Blk .902...0143
 12" WFR Watkins .902...1180
 EMIT Diaph. 1/2 LS .751...3722
 Diaph Assy. Rev. B/C .751...3806

REFERENCE STANDARD 4.5

TECHNICAL SPECIFICATIONS



REFERENCE STANDARD 4.5

